

# SAFETY DATA SHEET

Date Issued : 02/14/2023  
SDS No. : EZ Clor Filter Renew

## E-Z Clor Filter Renew

### 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** E-Z Clor Filter Renew  
**GENERAL USE:** Filter Cartridge Cleaner

**DISTRIBUTOR**

Alliance Trading, Inc.  
109 North Park Blvd., 4th Floor  
Covington, LA 70433

**24 HR. EMERGENCY TELEPHONE NUMBERS**

Chem-Tel 24-Hour Emergency # (800) 255-3924

### 2. HAZARDS IDENTIFICATION

**GHS CLASSIFICATIONS**

Corrosive to Metals, Category 1

**Health:**

Skin Corrosion/Skin Irritation, Category 2  
Serious Eye Damage/Eye Irritation, Category 1

**Environmental:**

Acute Hazards to the Aquatic Environment, Category 3  
Chronic Hazards to the Aquatic Environment, Category 3

**GHS LABEL**



Corrosion

**SIGNAL WORD:** DANGER

**HAZARD STATEMENTS**

H318: Causes serious eye damage.  
H412: Harmful to aquatic life with long lasting effects.  
H402: Harmful to aquatic life.  
H290: May be corrosive to metals.

**PRECAUTIONARY STATEMENT(S)**

**General:**

P390: Absorb spillage to prevent material damage.  
P273: Avoid release to the environment.  
P501: Dispose of contents/container to ...  
789508DQ: Dispose of contents/container to comply with local, state and federal regulations.  
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P302+P352: IF ON SKIN: Wash with plenty of water/...  
P332+P313: If skin irritation occurs: Get medical advice/attention.  
P310: Immediately call a POISON CENTER/doctor/...  
P234: Keep only in original packaging.  
P321: Specific treatment (see ... on this label).  
P406: Store in a corrosion resistant/...container with a resistant inner liner.  
P362+P364: Take off contaminated clothing and wash it before reuse.  
P264: Wash ... thoroughly after handling.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

## SAFETY DATA SHEET

Date Issued : 02/14/2023  
SDS No. : EZ Clor Filter Renew

## E-Z Clor Filter Renew

Chemical Name	Wt. %	CAS
Benzene, 1,1'-oxybis-,tetrapropylene Dervis., Sulfonated, Sodium Salts	4 - 5	119345-04-9
Hydrochloric Acid (Skin Corr. 1B, H314; Met. Corr. 1, H290; STOT SE 3, H335)	4.03	7647-01-0
EthylenediaminetetraAcetic Acid, Tetrasodium Salt	1.14	64-02-8
Sulfuric Acid Disodium Salt	< 0.1	7757-82-6
Sodium Hydroxide	0.03 - 0.051	1310-73-2
Sodium Chloride	< 0.03	7647-14-5
2,4-imidazolidinedione, 1,3-bis(hydroxymethyl)-5, 5-dimethyl-	< 0.03	6440-58-0
3(2h)-isothiszolone, 2-methyl-	< 0.0014	2682-20-4

## 4. FIRST AID MEASURES

**EYES:** Immediately flush eyes with plenty of water for at least 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately. Take care not to rinse contaminated water into the unaffected eye or onto the face.

**SKIN:** Immediately wash skin with plenty of water for at least 15 minutes. Remove contaminated clothing. Get medical attention if symptoms occur. Wash clothing before reuse.

**INGESTION:** Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

**INHALATION:** If symptoms occur, go into open air and ventilate area. Obtain medical attention if breathing difficulty persists.

## SIGNS AND SYMPTOMS OF OVEREXPOSURE

**EYES:** Causes permanent damage to the cornea, iris, or conjunctiva.

**SKIN:** Causes skin irritation.

**INGESTION:** May cause adverse effects.

## 5. FIRE FIGHTING MEASURES

**FLAMMABLE CLASS:** Not considered flammable but may burn at high temperatures.

**EXTINGUISHING MEDIA:** Water spray, fog, carbon dioxide (CO<sub>2</sub>), alcohol-resistant foam, or dry chemical. Do not use a heavy water stream. Use of heavy stream of water may spread fire.

**HAZARDOUS COMBUSTION PRODUCTS:** Carbon Oxides, Nitrogen Oxides, Sodium Oxides, Chlorides

**EXPLOSION HAZARDS:** Contact with metallic substances may release flammable hydrogen gas.

**FIRE FIGHTING PROCEDURES:** Use water spray to cool unopened containers.

**FIRE FIGHTING EQUIPMENT:** Firefighters should wear NIOSH/MSHA approved self-contained breathing apparatus and protective clothing.

**FIRE EXPLOSION:** Not considered flammable but may burn at high temperatures.

## 6. ACCIDENTAL RELEASE MEASURES

**SMALL SPILL:** Clean up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Absorb spillage to prevent material damage.

**LARGE SPILL:** Do not touch or walk on the spilled product. Stop leak, if possible without risk. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

**RELEASE NOTES:** Prevent entry into sewers and watercourses.

## 7. HANDLING AND STORAGE

**GENERAL PROCEDURES:** Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and when leaving work. Avoid breathing vapors, mist or spray. Do not get in eyes, on skin or clothing. Handle in accordance with good industrial hygiene and safety procedures.

**STORAGE:** Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low

## SAFETY DATA SHEET

Date Issued : 02/14/2023  
SDS No. : EZ Clor Filter Renew

## E-Z Clor Filter Renew

temperatures and incompatible materials. Store in corrosive resistant container with a resistant inner liner. Incompatible Materials include: Strong acids, strong bases, strong oxidizers, metals.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

## EXPOSURE GUIDELINES

## OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)

Chemical Name	EXPOSURE LIMITS			
	Type		ppm	mg/m <sup>3</sup>
Benzene, 1,1'-oxybis-,tetrapropylene Dervis., Sulfonated, Sodium Salts	OSHA PEL	TWA	[1]	[1]
	Supplier OEL	TWA	NL	NL
		STEL	NL	NL
Hydrochloric Acid (Skin Corr. 1B, H314; Met. Corr. 1, H290; STOT SE 3, H335)	OSHA PEL	TWA	7 mg/m <sup>3</sup>	
		STEL	ppm [2]	[2]
	ACGIH TLV	STEL	2 ppm [3]	[3]
	Supplier OEL	TWA	NL	NL
STEL		NL	NL	
Sodium Hydroxide	OSHA PEL	TWA	[1]	2 [1]
		STEL	[4]	[4]
	ACGIH TLV	TWA	[5]	2 [5]
	Supplier OEL	TWA	NL	NL
STEL		NL	NL	

## Footnotes:

1. NL = Not Listed
2. Ceiling
3. Ceiling (based on irritation and corrosion effects)
4. C = Ceiling
5. Ceiling.

**ENGINEERING CONTROLS:** Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

## PERSONAL PROTECTIVE EQUIPMENT

**EYES AND FACE:** Chemical goggles or safety glasses.

**SKIN:** Impervious clothing and protective gloves.

**RESPIRATORY:** If exposure limits are exceeded, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations.

**PROTECTIVE CLOTHING:** Chemically-resistant clothing.

**WORK HYGIENIC PRACTICES:** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**PHYSICAL STATE:** Liquid

**COLOR:** Clear

**pH:** < 1

# SAFETY DATA SHEET

Date Issued : 02/14/2023  
SDS No. : EZ Clor Filter Renew

## E-Z Clor Filter Renew

**FLASHPOINT AND METHOD:** Not Applicable.

**SOLUBILITY IN WATER:** Fully soluble.

**SPECIFIC GRAVITY:** 1.027 to 1.047

**VISCOSITY:** Water-like

### 10. STABILITY AND REACTIVITY

**REACTIVITY:** Direct sunlight, extremely high or low temperatures, and incompatible materials.

**STABILITY:** Stable at normal temperatures and pressures.

**CONDITIONS TO AVOID:** Direct sources of heat. Avoid high temperatures. Direct sunlight. Avoid contact with incompatible materials. Do not use in areas without adequate ventilation. Do not allow evaporation to dryness.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Thermal decomposition may produce: Carbon oxides, Nitrogen oxides, Sodium Oxides, Sulfur oxides and Chlorides.

**INCOMPATIBLE MATERIALS:** Strong acids, strong bases, strong oxidizers, metals. May be corrosive to metals.

### 11. TOXICOLOGICAL INFORMATION

#### ACUTE TOXICITY

**DERMAL LD<sub>50</sub>:** > 2000 mg/kg - Rabbit

**ORAL LD<sub>50</sub>:** > 2000 mg/kg - Rat

**SKIN CORROSION/IRRITATION:** Cause skin irritation.

**SERIOUS EYE DAMAGE/IRRITATION:** Causes serious eye damage. Irritating to skin.

#### CARCINOGENICITY

**IARC:** Hydrochloric Acid (7647-01-0) - 3

### 12. ECOLOGICAL INFORMATION

#### AQUATIC TOXICITY (ACUTE)

**96-HOUR LC<sub>50</sub>:** 45.4 mg/L (Oncorhynchus mykiss [static])

**96-HOUR EC<sub>50</sub>:** 40 mg/L (Crustacea)

**BIOACCUMULATION/ACCUMULATION:** Not Established

**GENERAL COMMENTS:** Mobility in soil: No additional information available.

Persistence and Degradability - May cause long-term adverse effects in the environment.

Avoid release into the environment.

### 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** Disposal must be made according to official regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

**PRODUCT DISPOSAL:** Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

**EMPTY CONTAINER:** Container may remain hazardous when empty. Continue to observe all precautions.

### 14. TRANSPORT INFORMATION

#### DOT (DEPARTMENT OF TRANSPORTATION)

**PROPER SHIPPING NAME:** Hydrochloric Acid

**PRIMARY HAZARD CLASS/DIVISION:** 8

## SAFETY DATA SHEET

Date Issued : 02/14/2023  
SDS No. : EZ Clor Filter Renew

## E-Z Clor Filter Renew

UN/NA NUMBER: 1789

PACKING GROUP: III

NAERG: 157

LABEL: Corrosive

## AIR (ICAO/IATA)

SHIPPING NAME: Hydrochloric Acid

UN/NA NUMBER: 1789

PRIMARY HAZARD CLASS/DIVISION: 8

PACKING GROUP: III

ERG: 8L

LABEL: 8

## VESSEL (IMO/IMDG)

SHIPPING NAME: Hydrochloric Acid

UN/NA NUMBER: 1789

PRIMARY HAZARD CLASS/DIVISION: 8

PACKING GROUP: III

EmS: F-A, S-B

## 15. REGULATORY INFORMATION

## UNITED STATES

## SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

313 REPORTABLE INGREDIENTS: 1% (acid aerosols including mists, vapors, gas, fog, and other airborne forms of any particle size).

## 302/304 EMERGENCY PLANNING

EMERGENCY PLAN: Listed on Inventory List.

THRESHOLD QUANTITY: 500 (gas)

## CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

Chemical Name	Wt. %	CERCLA RQ
Hydrochloric Acid (Skin Corr. 1B, H314; Met. Corr. 1, H290; STOT SE 3, H335)	4.03	5,000 lbs.
Sodium Hydroxide	0.03 - 0.051	1,000 lbs.

CERCLA RQ: 5000 lbs - hydrochloric acid.

## TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA STATUS: Active.

## STATES WITH SPECIAL REQUIREMENTS

Chemical Name	Requirements
Sodium Hydroxide	Massachusetts Hazardous Substance New York Hazardous Substance Minnesota Hazardous Substance Washington PELS for Air Contaminants

## 16. OTHER INFORMATION

Date Prepared: 02/14/2023

# SAFETY DATA SHEET

Date Issued : 02/14/2023  
SDS No. : EZ Clor Filter Renew

## E-Z Clor Filter Renew

---

### HMIS RATING

HEALTH	<input type="checkbox"/>	1
FLAMMABILITY	<input type="checkbox"/>	1
PHYSICAL HAZARD	<input type="checkbox"/>	0
PERSONAL PROTECTION	<input type="checkbox"/>	Y

**MANUFACTURER DISCLAIMER:** Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).